



BDW Marine LLP  
Units 1 & 2 Poplars Farm  
Aythorpe Roding  
Dunmow  
Essex CM16 1RY

Tel: 01647 253204  
Fax: 0845 280 2195  
Email: [enquiries@Premier-Paints.co.uk](mailto:enquiries@Premier-Paints.co.uk)

## Premier Performance Extra Antifouling

### PRODUCT DATA

#### **Description:**

Copper based antifouling. Premier Performance Extra Antifouling is semi-hard to enable use in most craft up to 35 knots but still able to refresh its surface with some mild erosion. Proven performance for all types fouling in all waters. This product is self-priming when topping up existing (similar copper based) antifouling; otherwise Premier Antifouling Primer or Premier Multi-Purpose Metallic Primer is required. Also suitable for long distance cruisers or racers via the semi-hard nature of the paint system. Available in 2.5L or 450ml for use as boot-top or small extra quantity

**Area of use:** Boat hulls

#### **Substrates:**

GRP, wood, steel and ferro cement. Not suitable for aluminium or galvanised surfaces.

#### **Packing:**

1 litre and 2.5 litre

#### **Physical Constants:**

Colour: Black, Dark Blue, Light Blue, Red and Steel White

Finish: Matt

Volume solids: 75%

Theoretical spreading rate: 10 sq.metres per litre

Flash point: 42°C

Specific gravity: 1.80

Dry to touch: 2 hours

Over-coating time: 6 hours

Should be launched within 2 – 3 months dependent on ambient temperature.

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. **The physical constants** are subject to normal manufacturing tolerances.*

#### **Application Details:**

Application method: Brush, Conventional spray, Airless spray, Roller.

Thinner: Premier Antifouling Thinners

Cleaning of tools: Premier Antifouling Thinners

**Surface condition:** The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease, oil and salt.

*Please refer to the Material Safety Data Sheet for further information. For additional guidance please contact your local Technical Sales Representative.*